

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

1. (Currently Amended) A toilet apparatus comprising:
 - a) a base portion having a width of about 21.5 inches and a length of about 29.05 inches, wherein the interior of the base portion further comprises at least two a-reinforced portions, each reinforced portion disposed on a lateral side of the base portion and comprising a plurality of ceramic walls vertically extending from a bottom of the base portion to the bowl portion;
 - b) a bowl portion attached to the base portion wherein the width of the outer portion of the bowl is about 25 inches, the length of the outer portion of the bowl is about 32 inches, and wherein the outer portion of the bowl is substantially aligned with a bottom of the base portion;
2. (Cancelled)
3. (Previously Amended) A toilet apparatus of Claim 1 wherein the reinforced portion is aligned with an anchorage point operable to attach the toilet apparatus to a flat surface.
4. (Cancelled) ~~A toilet apparatus of Claim 3 further comprising a plurality of anchorage points and a corresponding plurality of reinforced portions.~~
5. (Cancelled) ~~A toilet apparatus of Claim 4 wherein two anchorage points and two corresponding reinforced portions are located on opposite sides of the base portion.~~

6. (Currently Amended) A toilet apparatus of Claim ~~5~~3 wherein the two anchorage points are located about 8.95 inches from a line bisecting the toilet apparatus into symmetrical left and right sides.

7. (Previously Amended) A toilet apparatus of Claim 1 wherein a width of the reinforced portion is about 2.9 inches and a length of the reinforced portion is about 2.4 inches.

8. (Original) A toilet apparatus of Claim 1 wherein a thickness of a wall of the base portion is at least about .39 inches.

9. (Original) A toilet apparatus of Claim 1 wherein the height of the toilet apparatus is greater than about 17 inches.

10. (Cancelled) ~~A toilet seat comprising~~
- ~~a) an inner and an outer rim;~~
 - ~~b) two vertically extending rigid members located between the outer and inner rims of the left side and the right side of the toilet seat, wherein the vertically extending rigid members are positioned for alignment with an interior edge of a toilet bowl as to prevent lateral displacement of the seat when in use and wherein the vertically extending rigid members are integrally formed in the seat.~~

11. ~~(Cancelled) A toilet seat of Claim 10 wherein a width of the toilet seat is about 25 inches and a length of the toilet seat is about 24.5 inches.~~

12. ~~(Cancelled) A toilet seat of Claim 10 wherein a width of an aperture formed by the inner rim of the toilet seat is less than about half the width of the toilet seat.~~

13. ~~(Cancelled) A toilet seat of Claim 10 wherein a length of the aperture formed by the inner rim of the toilet seat is greater than about two thirds the length of the toilet seat.~~

14. ~~(Cancelled) A toilet seat of Claim 10 wherein a width of the aperture formed by the inner rim of the toilet seat is about 8.2 inches and a length of the aperture formed by the inner rim of the toilet seat is about 16.7 inches.~~

15. ~~(Cancelled) A toilet seat of Claim 10 further comprising a plurality of radially disposed support members on a bottom surface of the toilet seat.~~

16. (Currently Amended) A toilet comprising:
a) a base portion having a width of about 21.5 inches and a length of about 29.05 inches, wherein the interior of the base portion further comprises at least two a-reinforced portions, each reinforced portion disposed on a lateral side of the base portion and comprising a plurality of ceramic walls vertically extending from a bottom of the base portion to the bowl portion;

b) a bowl portion attached to the base portion wherein the width of the outer portion of the bowl is about 25 inches, the length of the outer portion of the bowl is about 32 inches, and wherein the outer portion of the bowl is substantially aligned with a bottom of the base portion; and

c) a toilet seat comprising an inner and an outer rim and further comprising two vertically extending rigid members located between the outer and inner rims of the left side and the right side of the toilet seat, wherein the vertically extending rigid members are positioned for alignment with an interior edge of a toilet bowl as to prevent lateral displacement of the seat when in use and wherein the vertically extending rigid members are integrally formed in the seat.

17. (Cancelled)

18. (Previously Amended) A toilet of Claim 16 wherein the reinforced portion is aligned with an anchorage point operable to attach the toilet apparatus to a flat surface.

19. (Cancelled) ~~A toilet of Claim 18 further comprising a plurality of anchorage points and a corresponding plurality of reinforced portions~~

20. (Cancelled) ~~A toilet of Claim 19 wherein two anchorage points and two corresponding reinforced portions are located on opposite sides of the base portion.~~

21. (Currently Amended) A toilet of Claim 2018 wherein the two anchorage points are located about 8.95 inches from a line bisecting the toilet apparatus into symmetrical left and right sides.

22. (Previously Amended) A toilet of Claim 16 wherein a width of the reinforced portion is about 2.9 inches and a length of the reinforced portion is about 2.4 inches.

23. (Original) A toilet of Claim 16 wherein the thickness of a wall of the base portion is at least about .39 inches.

24. (Original) A toilet of Claim 16 wherein a width of the toilet seat is about 25 inches and a length of the toilet seat is about 24.5 inches.

25. (Original) A toilet of Claim 16 wherein a width of an aperture formed by the inner rim of the toilet seat is less than about half of a width of the toilet seat.

26. (Original) A toilet of Claim 16 wherein a length of the aperture formed by the inner rim of the toilet seat is greater than about two-thirds of a length of the toilet seat.

27. (Previously Amended) A toilet of Claim 16 wherein a width of the aperture formed by the inner rim of the toilet seat is about 8.2 inches and a length of the aperture formed by the inner rim of the toilet seat is about 16.7 inches.

28. (Original) A toilet of Claim 16 further comprising a plurality of radially disposed support members on a bottom surface of the toilet seat.

29. (Original) A toilet of Claim 16 wherein the height of the toilet is greater than about 17 inches.